IP65 TIS 220V AC 50Hz 40,000hrs. Lifetime

Housing : Compression moulded glass reinforced polyester (GRP) **Gear tray :** Die-formed cold-rolled steel finished with high gloss baked white polyester powder **Diffuser :** Injection moulded clear prismatic UV stablilized polycarbonate (PC) with 2 part stainless steel clips
Lamp Holder : G13 for T8 LED **Mounting :** Screw fixed direct to mounting Surface , Snap fit into Stainlesssteel Suspension brackets
Applications : Can be use in cold storage room -30° C ambient temperrature

Surface cold storage luminaire

Model	LLCSE/1S	LLCSE/1L	LLCSE/2S	LLCSE/2L
Power consumption	9W*	18W**	18W*	36W**
Source	LED T8			
Lamp color	Cool white 4000K 908 lm	Cool white 4000K 1815 lm	Cool white 4000K 1795 lm	Cool white 4000K 3590 lm
	Cool daylight 6500K 908 lm	Cool daylight 6500K 1815 lm	Cool daylight 6500K 1795 lm	Cool daylight 6500K 3590 lm
Replacement of	T5 1x14W T8 1x18W	T5 1x28W T8 1x36W	T5 2x14W T8 2x18W	T5 2x28W T8 2x36W

Remark * L&E 9W 1050 Lumen LED TUBE T8, ** L&E 18W 2100 Lumen LED TUBE T8



Mountain creek golf resort & residences : Thailand

Accessory for luminaire

Cable gland

Suspension bracket

Polycarbonate clip

Stainless clip

Accessory part

LLCSE/1S

LLCSE/1L



LLCSE/2S



LLCSE/2L