

LED Lamp



TIS LED-BULB/LPF

Application

This LED lamp is designed to replace conventional lamp which is safe cost and save energy depending on each lamp types. There is no UV, long lifetime, etc.

Specification


Housing Description	Aluminium inside cover with plastic Do not use with enclosed fixtures Operating temperature -20 / +40 degree
Body Colour	White
Power	5-15W , Pf 0.5 ,CRI >80
Light Source	LED-SMD
Lamp Holder	E27
Colour Temperature	3000K/4000K/6500K
Lamp Output	5W:470lm,510lm 7W:630lm,690lm 9W:810lm,850lm 10W:980lm 11W:1050lm 13W:1350lm 15W:1450lm
Control Gear	Built-in driver
Power Supply	220VAC,50Hz
LED Lifetime	25,000 hrs.

Ordering Data

Model	Watt
L&E#LED-Bulb-470LM/830/5W/E27	5W
L&E#LED-Bulb-510LM/865/5W/E27	5W
L&E#LED-Bulb-630LM/830/7W/E27(G3)	7W
L&E#LED-Bulb-690LM/865/7W/E27(G3)	7W
L&E#LED-Bulb-810LM/830/9W/E27(G3)	9W
L&E#LED-Bulb-850LM/840/9W/E27(G3)	9W
L&E#LED-Bulb-850LM/865/9W/E27(G3)	9W
L&E#LED-Bulb-980LM/865/10W/E27 (G3)	10W
L&E#LED-Bulb-1050LM/830/11W/E27(G3)	11W
L&E#LED-Bulb-1050LM/840/11W/E27(G3)	11W
L&E#LED-Bulb-1050LM/865/11W/E27(G3)	11W
L&E#LED-Bulb-1350LM/830/13W/E27	13W
L&E#LED-Bulb-1350LM/865/13W/E27	13W
L&E#LED-Bulb-1450LM/830/15W/E27	15W
L&E#LED-Bulb-1450LM/865/15W/E27	15W




A60 (5/7/8/9/10/11W)



113

A70(13/15W)



130

Related Products



Recessed Downlight

Recessed Downlight

Surface downlight

Surface downlight