

LED Canopy / Tunnel



TIS CAL510

Application

Canopy is designed to illuminate tunnels, underpasses, warehouses, garages, indoor gymnasiums, recreational and competition sport fields, etc.

Specification

| | |
|---------------------------|--|
| Housing | Die-cast aluminium |
| Front Cover | Clear toughened glass |
| Finishing | Powder coated in black |
| Lens | Acrylic (PMMA) |
| Gasket | Silicone rubber |
| Dimension | 250x500x180 mm. |
| Mounting | Surface |
| Power | 35/55/70W |
| Light Source | LED Module |
| Colour Temperature | 3000/4000/5700K |
| Luminaire Output | 35W : 4900 lm (55 degree) 35W : 4550 lm (90 degree) 55W : 7700 lm (55 degree) 55W : 7150 lm (90 degree) 70W : 9800 lm (55 degree) 70W : 9100 lm (90 degree) |
| Beam Angle | 55/90 degree |
| Control Gear | Built-in driver |
| Power Supply | 220-240VAC, 50Hz |
| Power Factor | >0.95 |
| IP Rating | 66 |
| Luminaire Lifetime | 50,000 hrs. |
| Equivalent | 35W : MH 70W 55W : MH 100W 70W : MH 150W |

Ordering Data

| Model | Watt |
|--------------|------|
| CAL510-35LED | 35W |
| CAL510-55LED | 55W |
| CAL510-70LED | 70W |

