

LED Canopy / Tunnel



TIS CAL511

Application

Canopy is designed to illuminate tunnels, underpasses, warehouses, garages, indoor gymnasiums, recreational and competition sport fields, etc.

Specification

| | |
|---------------------------|--|
| Housing | Die-cast aluminium |
| Front Cover | Clear toughened glass |
| Finishing | Powder coated in black |
| Lens | Acrylic (PMMA) |
| Gasket | Silicone rubber |
| Dimension | 290x580x180 mm. |
| Mounting | Surface |
| Power | 105/125/150W |
| Light Source | LED Module |
| Colour Temperature | 3000/4000/5700K |
| Luminaire Output | 105W : 15225 lm (55 degree) 105W : 14175 lm (90 degree) 125W : 17500 lm (55 degree) 125W : 16875 lm (90 degree) 150W : 20250 lm (55 degree) 150W : 19500 lm (90 degree) |
| Beam Angle | 55/90 degree |
| Control Gear | Built-in driver |
| Power Supply | 220-240VAC, 50Hz |
| Power Factor | >0.95 |
| Insulation Class | I |
| IP Rating | 66 |
| Luminaire Lifetime | 50,000 hrs. |
| Equivalent | MH 250W |

Ordering Data

| Model | Watt |
|---------------|------|
| CAL511-105LED | 105W |
| CAL511-125LED | 125W |
| CAL511-150LED | 150W |

